# **Ranger 1/Ranger 3**

#### Ranger 1



## STANDARD FEATURES:

- · ABS plastic case, weighs less than 1 lb
- · Large vernier knob, smooth 10 turn potentiometer
- Ideal tool for troubleshooting a scale system, bench testing stability of indicators and setpoint simulation

## **SPECIFICATIONS:**

Variable Range:

#### 0-3 mV/V

Impedance:

700 ohms nominal

**Connectors:** 

Binding posts suitable for banana plug or 14 gauge wire

### **PART NUMBER/PRICE**

PART#	DESCRIPTION	PRICE
68029	Ranger 1 Variable Range Simulator	\$130.00

• Binding posts are color coded to ISA S37.8

4.5" L x 3.5" W x 1.25" H (114.3 mm W x 88.9 mm H x 31.8 mm D)

standard

**Temperature Coefficient:** 

±100 ppm/ °C

Dimensions:

## **OPTIONS/ACCESSORIES**

PART#	DESCRIPTION	PRICE
21116	Cable with banana plugs	\$55.00

#### **Ranger 3**



## **STANDARD FEATURES:**

- · ABS plastic case, weighs less than 1 lb Fixed rotary switch, -0.5 mV/V to 4.5 mV/V in 9
- steps of .5 mV/V per step
- · Ideal tool for calibrating the indicator A-D offset and gain setting

## **SPECIFICATIONS:**

Fixed Steps: **Temperature Coefficient:** -0.5 mV/V-4.5 mV/V range ±5 ppm/ °C Impedance: Dimensions: 4.5" L x 3.5" W x 1.25" H (114.3 mm W x 88.9 mm H x 31.8 mm D) 350 ohms nominal Nonlinearity: Less than .02% **Connectors:** Binding posts-suitable for banana plug or 14 gauge wire

## **PART NUMBER/PRICE**

PART#	DESCRIPTION	PRICE
68030	Ranger 3 Calibration Simulator	\$345.00

## **OPTIONS/ACCESSORIES**

PART#	DESCRIPTION	PRICE
21116	Cable with banana plugs	\$55.00

An ISO 9001 Registered Company © 2013 Rice Lake Weighing Systems 01/13 Prices and specifications subject to change without notice. Visit ricelake.com for current prices.



• A-D calibration steps for-0.5 mV/V for offset and

· Used in testing, troubleshooting and calibrating

Binding posts are color coded to ISA S37.8

4.5 mV/V for gain

standard

digital weight indicators

WEIGHING SY