

# **DGT1S PLUS**

### "DGT1S PLUS": MULTIFUNCTION DIGITAL WEIGHT TRANSMITTER



Compact multifunction weight transmitter, for DIN rail mounting. It allows the direct reading and diagnostics of the connected weighing system. The wide range of available interfaces makes the integration of the weighing in any automation system easier and safer.

Available in the following versions:

PROFINET | ETHERNET/IP | MODBUS/TCP |

ETHERCAT | PROFIBUS | DEVICENET |

CANOPEN | ANALOG OUTPUT | RS485

Approvals:

CE-M EN 45501, OIML R-76, OIML R-61 (MID),

CE-M EN 45501, OIML R-76, OIML R-61 (MID)
OIML R-51 (MID)

Integrated WebServer as standard, for configuration, diagnostics and data backup.

#### Working in cooperation with:

ASSOCIATED SCALE SERVICES PTY LTD

47 MORETON ST. - 4110 - HEATHWOOD - AUSTRALIA Tel. +617 3277 0077 Fax. +617 3272 0363 sales@associatedscales.com.au The best solution for advanced industrial applications

### **TECHNICAL FEATURES**

- Number of scales/channels: 1
- Calibration:
  - Theoretical (mV\V)
  - With sample weights
  - Via Web server
- Conversion rate:
  - Up to 400 Hz
- Maximum number of load cells: Up to 16x350Ω
- Minimum sensitivity:
  - High resolution 0,01 μV/d
  - Legal for trade 0,3 μV/e
- Number of legal-for-trade divisions:
- Up to 10,000e or multi-field 2x3,000eLoad cell excitation voltage: 5 V
- Communication ports:
  - 1 micro-USB port (device) (Mod. with fieldbus)
  - 1 RS485 port (Mod. DGT1SP / DGT1SP-AN)
- Communication protocols: Modbus RTU, ASCII or fieldbus
- Communication rate:
  - On serial port up to 325 Hz
  - On Fieldbus up to 16 Hz
- PC programs for configuration: DiniTools
- Display: Red LED 8 mm, 6 characters
- Keyboard: 5-key mechanical
- Housing: ABS
- Power supply: 12÷24 Vdc, 5 W
- Maximum power: 4,1 W
- Operating temperature range:
- For internal use -20°C ÷ +60°C
- Approved -10°C ÷ +40°C
- Max. humidity: 85%.

### **INPUTS/OUTPUTS**

- Analogue output: 16 bit (Model DGT1SP-AN)
  - 4÷20mA
  - 0÷10Vdc
- Digital outputs: n. 4 OUT, configurable
- Digital inputs: n. 2 IN, configurable

### **CERTIFICATIONS**

- 2014/30/EU EMC
- 2014/35/EU LVD
- 2011/65/EU RoHS
- OIML R61 MID
- OIML R51 MID
- OIML R76
- EU Type Examination Certificate (2014/31/EU)

## **UL CERTIFIED WEIGHT TRANSMITTERS**

• UL certified transmitters are available, <u>click here</u> to find out the full range.





**DINI ARGEO FRANCE sarl**France

DINI ARGEO GMBH Germany **DINI ARGEO UK Ltd**United Kingdom

DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



#### **COMPANY HEADQUARTERS**

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena • Italy Tel. +39.0536 843418

#### ASSOCIATED SCALE SERVICES PTY LTD

47 MORETON ST. - 4110 - HEATHWOOD - AUSTRALIA

Tel. +617 3277 0077 Fax. +617 3272 0363

sales@associatedscales.com.au

SALES AND TECHNICAL ASSISTANCE SERVICE