

3590EGT3GD

3590EGT 3GD "TOUCH" : TOUCH SCREEN INDICATOR FOR ATEX 2 & 22 ZONES



Weight indicator with a big touch screen display, for ATEX 2 & 22 areas classified at risk of explosion. Protection methods according to ATEX II 3G Ex nR IIB T6 Gc X for gases
 ATEX II 3D Ex tc IIIC T85°C Dc IP68 X for dust. Suitable for advanced industrial applications, it's fitted with 3 serial ports, configurable printouts and integrated alibi memory. CE-M approvable (OIML R-76 / EN 45501).

Working in cooperation with:

ASSOCIATED SCALE SERVICES PTY LTD
 47 MORETON ST. - 4110 - HEATHWOOD - AUSTRALIA
 Tel. +617 3277 0077 Fax. +617 3272 0363
sales@associatedscales.com.au

**The best solution
 for advanced industrial
 applications**

MAIN FEATURES

- 5,7" colour touch screen display
- Multilanguage software
- 15-key alphanumerical waterproof keyboard
- 3-way control light
- Selectable QWERTY, AZERTY or QWERTZ keyboard integrated in the touch screen
- Stainless steel waterproof enclosure, with new IP68 protection system
- Dimensions: 280x143x185mm
- Suitable for use on the table, column or wall
- Real time clock and permanent data storage
- Fitted alibi memory, integrated on the motherboard
- Slot for built-in micro SD for recording the configuration, logos, and customized screens (upon request)
- Functions available with DINITOOLS utility
 - Configuration, data entry and print formatting
 - Recording and filing of all the information on PC
 - Complete retrieval of the configuration
 - Instrument calibration with numeric values
 - Customization of the screens
- 24-bit A/D converter, 4 channels, up to 3200 conv./sec. and up to 8 signal linearisation points
- 4 independent analogue channels for reading of the weight
- Connection with up to 16 analogue load cells of 350 Ohm (45 load cells of 1000 Ohm)
- Up to 10.000e OIML or 3 x 3000e @ 0,3 $\mu\text{V/e}$ CE-M legal for trade
- Up to 1.000.000 displayable divisions for internal factory use, with internal resolution up to 3.000.000 points
- Connectable to printers and labellers with free programming of the printout formats
- Power supply from 110-240Vac line or external rechargeable battery (recharge in safety zone).

MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76
- OIML R51 - MID
- OIML R134 (AF09)
- Australian legal for trade certificate of approval (NMI S788)

APPLICATION SOFTWARE

- SUPPLIED AS STANDARD:
- AF01: Totalization and formula weighing

OPTIONAL:

- AF02: Pieces/quantity counting
- AF03: Weighbridges - Input/Output vehicle
- AF04: Statistical checking of prepackaged goods
- AF05: Price computing and industrial labelling
- AF08: Wheel and axle static weighing with 2 or various platforms
- AF09: Dynamic and static axle weighing with 2 platforms
- BATCH1: Single product dosage systems in loading and unloading
- BATCH: Multicomponent dosage systems in loading and unloading (IOEXPB board must be included)

I/O SECTION

- Two RS232 serial ports, for connection to printer, radio module, PC or PLC, badge reader or remote scale.
- One RS485/RS232 serial port, for connection to printer, PC, PLC, or digital load cells.
- 4 optoisolated outputs, up to 16 with optional board.
- 2 optoisolated inputs, up to 8 with optional board.
- Modbus RTU Interface.
- Analog output DAC16O needs the expansion board IOEXPB.

Optionals:

- Profibus or Modbus/TCP interface to install in safety zone.
- External Profinet, Ethernet/IP, EtherCAT, CANopen and DeviceNet interface to install in safety zone. (optional, only with standard AF01 weighing program).

AVAILABLE LANGUAGES

- Menu selectable languages:
IT, EN, FR, DE, ES, PT, PL*

* Polish available only on EGT-AF01, EGT-AF02, EGT-AF03, EGT-AF04, EGT-AF09, EGT-BATCH, EGT-BATCH1

Code pages available for the translation of messages and screens, using the Custom Language Tool program (downloadable in the Download section):

- Windows 1252: EN, GA, IT, NO, PT, ES, SV, DE, FI, IS, FR, NL, SL
- Windows 1250: PL, CS, SK, HU, SL, SH, RO, SQ, EN, DE
- Windows 1251: RU, UK, BE, BG, SR, MK, EN
- Windows 1253: EL, EN
- Windows 1258: VI, EN, FR

Text (LOT)

|

Esc	`	<	/]	Clear	BkSp			
1	2	3	4	5	6	7	8	9	0
Q	W	E	R	T	Y	U	I	O	P
A	S	D	F	G	H	J	K	L	;
2 [^] _F	Z	X	C	V	B	N	M	,	.
Shift	←						→	OK	

QWERTY keyboard integrated into the Touch Screen display.



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

ASSOCIATED SCALE SERVICES PTY LTD

47 MORETON ST. - 4110 - HEATHWOOD - AUSTRALIA

Tel. +617 3277 0077 Fax. +617 3272 0363

sales@associatedscales.com.au

SALES AND TECHNICAL ASSISTANCE SERVICE