

LTW_COMPACT

LTW COMPACT FORKHOLDER PLATE WITH INTEGRATED WEIGHING



Weighing plate for forklift, with fixing rail DIN15173 - FEM class II, to transform a normal forklift into a mobile scale. Fitted with COMPACT weight indicator in the cabin, versatile and easy to use. Available also in approved version for legal-for-trade use.

**The best solution
for advanced industrial
applications**

WEIGHING FEATURES

- Max. permissible overload: over 300% of the maximum capacity, with overload protection nuts in case of hinge breaking.
- Accuracy:
 - > internal use: +/- 0.05% of the capacity
 - > approved: according to CE certification (Directive 2014/31/EU)
- Max. horizontal inclination (tilting): +/- 2° with the same precision characteristics.

WHY CHOOSE LTW COMPACT DINI AR GEO

- The weighing plate is the most robust solution for weighing and handling loads in the warehouse.
- Strong and sturdy, it is equipped with an integrated protection system against overloads and accidental impacts.
- The standard COMPACT indicator, easy to install in the cabin, is useful to read the weighing data.
- Suitable for standard FEM2A and FEM2B forks.
- Built with 2 Dini Argeo load cells, in stainless steel, with IP68 protection.
- Available in approved version for legal-for-trade use.
- Available in wired or Bluetooth version, completely wireless.

TECHNICAL FEATURES

- Plate dimensions 910 x 407 x 110 mm
- Weight 184 kg
- Max. fork length: 1100 mm
- Max. center of gravity displacement: 55 mm
- Plate supporting structure made of thick steel
- Hermetic junction box
- Extensible cable as standard (length 5 m)



	LTP	ELP	TWIN FORKS	LTW
Weighing technology	Hydraulic pressure	Hydraulic pressure	Load cells	Load cells
Application	Forklifts	Electric pallet trucks and stackers	Forklifts	Forklifts
CE-M approved	No	No	Yes	Yes
Resolution (internal use)	From 5 kg	From 1 kg	1 / 2 kg	0,2 / 0,5 kg 0,5 / 1 kg
Resolution (CE-M approved)	-	-	2 / 5 kg	1 / 2 kg 2 / 5 kg
Precision	± 20 kg from 0,5% to 5%	± 20 kg from 0,5% to 5%	± 2 kg	± 0,05 % of the max. capacity

COMPACT WEIGHT INDICATOR FEATURES

- Weight indicator in ABS with backlit LCD 25mm display with 6 high contrast digits and icons for showing the active functions.
- Fitted with fixing bracket for mounting in the cabin.
- Functional waterproof keypad with 5 keys.
- Easy to clean ABS IP68 enclosure, resistant to harsh and corrosive environments.
- Visual and audible overload indication.
- Auto-off (energy saving): 5 minutes adjustable or deactivable.
- Power supply directly from the forklift (optional power supply available)
- Optional printer complete with fixing bracket for mounting in the cabin.

DISPLAY ON THE WEIGHING PLATE (Bluetooth version)

- Backlit 25mm LCD display with 6 high-contrast digits and icons for indicating active functions.
- ABS IP68 case, easy to clean and resistant in harsh and corrosive environments.
- Communication with the weight indicator in the cabin through Bluetooth.
- Power supply through internal rechargeable battery, with 60h working autonomy and external battery charger provided as standard.

DETAIL 1



Forks not included.

VERSIONS

Available versions

	Code	Max (kg)	d (kg)	M (kg)
	LTWC15	600 / 1500	0,2 / 0,5	1 / 2
	LTWC25	1500 / 2500	0,5 / 1	2 / 5
	LTWC15BTH	600 / 1500	0,2 / 0,5	1 / 2
	LTWC25BTH	1500 / 2500	0,5 / 1	2 / 5

NOTE: Approved divisions obtainable only with the ECEMLTW option.



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE