

FEET PADS TO LOCK THE WEIGH PAD INTO POSITION 125MM CHANNEL WITH END CAPS TO INCREASE PROTECTION AROUND THE LOAD CELL



Water Resistant Plug used for indicator connections

Specifications

| Construction | ZINC PLATED Mild Steel |
|-------------------|---|
| | Optional : Stainless Steel |
| Foot | STAINLESS STEEL |
| Load Cell | 4 x 2000kg Anyload Load Cells 563YH |
| | Optional : 563YS Stainless Steel Load Cell |
| Length | VARIED From 400mm to 1500mm |
| Width (Per Beam) | 1025mm |
| Capacity | 3000kg x 1kg (Custom Welcome) |
| Indicator Options | Option 1: Supply Weigh FR-230 - Power Adaptor |
| (note included in | Option 2: Supply Weigh FR-271 - Power Adaptor |
| standard pricing) | Option 3: Rice Lake 480 Series - 240VAC Power GPO |
| | Option: Rechargeable Battery |
| | Option: Analogue Output |

ASSOCIATED SCALE SERVICES www.associatedscales.com.au 07 3272 0077 Associated Scale Services Pty Ltd Ph:+61 (0)7 3272 0077 Email: info@associatedscales.com.au Web: www.associatedscales.com.au